10.901ACT | Crayon Grey



TOTAL WRAP | Specialty Series (Gloss)

Features

10.901ACT | Crayon Grey is a 100 micron gloss cast PVC film. This Total Wrap product has been developed specifically for the vehicle wrapping market. By utilising cutting edge technology to combine the special PVC compounds together with high quality pigments, we can offer a film with incredible dimensional stability & long-term durability. Typical applications include vehicle graphics & signage projects that require an exterior service life of 7 years. This film is suitable for both indoor & outdoor environments.

10.901ACT | Crayon Grey is available in 1524mm (width) x 25m & 50m (length) rolls.

iSee2 ACT or Air Channel Technology liner offers the benefits of reduced wrinkling and air bubbles during the application of the vinyl. On top of this advantage, the ACT technology increases the repositionability and "slideability" for exact positioning. All these iSee2 benefits occur without decreasing the adhesive strength when adhering to curved surfaces.

Technical & Performance Information

Film Thickness	100 micron
Adhesive Thickness	25 micron
Total Thickness	125 micron
Adhesive type	Semi-permanent clear solvent based acrylic
Release Liner	145 gsm PE embossed ACT kraft liner
Artificial Weathering *	> 7 years
Film Tensile Strength MD	> 14 N/mm²
Film Elongation MD	> 130%
Adhesion to steel (20 mins / 180°)	5 N/25mm
Adhesion to steel (24 hrs / 180°)	15 N/25mm
Dimensiontal Stability	< 0,3 mm
Application Temperature	+10 to +25°C
Service Temperature	-40 to +90°C
* equivalent to vertical exposure in Mid-European climate	

Printed Liner

	www.isee2.eu
iS	26 5
Air Cha	nnel Technology

Warranty

Groendreef 35 9880 Aalter, Belgium T +32 9 216 67 00 E info@iSee2.eu W www.iSee2.eu iSee2 warrantees our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user stores the material in the original boxes (out of direct sunlight) from our factory. We also recommend to store our material at 21°C with 50% relative humidity. iSee2 only warrantees our products to be free from defects in workmanship or defects in iSee2 material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise shall be assumed by the seller or manufacturer. User assumes all risk and liability in connection herewith. All data values quoted above are typical and should not be used to deem the product defective, if measured values are different.