

# Mactac Protect Pro

Perfection loves protection



Mactac  
Protect  
Pro

Preserve and protect with Mactac Protect Pro. Featuring a durability of up to 10 years\*, self-healing and an anti-yellowing top coat, this vehicle paint protection film is ideal for a lasting, pristine protection.

With a total thickness of 203 microns, the Mactac Protect Pro is ready to preserve the vehicle paint from daily wear & tear. Minor scratches fade away due to the self-healing functionality (activated by heat) and supports to keep the vehicle looking great.

The anti-yellowing top coat is particularly resistant to UV radiation and staining. After application, one will find that the film is almost invisible due to its high-gloss finish.

During wet application Mactac Protect Pro has a good slide ability supporting applicators with the positioning of the material on the substrate. Good conformability and low-tack contributes to the ease of the application.

Mactac Protect Pro is available in 1.52 m width x 15 m length and comes with a protective sheet on the face layer.

## Advantages on applied vehicle parts

- Supports preventing paint damage during daily wear & tear
- Helps to protect a vehicles value
- Assists to retain the pristine appearance of a vehicle
- Good conformability and low tack contributes to the ease of application

\* Vertical exposure, Zone 1.



# Mactac Protect Pro



## Protection Zones

Mactac Protect Pro is suitable for full or partial vehicle wrapping especially where stone chips & minor debris is prone to hit the vehicle or other minor impacts are expected. For instance the roof, hood or rear from staining from above.

## Mactac Protect Pro offers advanced performance:

### Durability



- Up to 10 years (Vertical exposure, Zone 1)

### Anti-Yellowing top coat



- Supports UV & Stain Resistance

### Optical Appearance



- High gloss
- Transparent finish
- Good optical uniformity

### Self-Healing (activated by heat)



- Minor & Mild Scratches

### Water Repelling



- Helps to facilitate cleaning

### Wet Application



- Conformable
- Low tack

For further information, please refer to the technical data sheet.



**Product code**  
CK1550001



**Total thickness**  
203 microns



**Liner** PET Liner & PET  
Protective Sheet



**Core Size**  
3 inch



**Size** 1.52 m width  
x 15 m length

©2022 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.

All Mactac statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Mactac products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. All Mactac products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>



Email: [mactac.europe@mactac.eu](mailto:mactac.europe@mactac.eu) | [mactacgraphics.eu](http://mactacgraphics.eu)

**mactac** 