

Product information

September 2011

Display Pop up film SB

340 µm

Material Description

Heavy quality block out film with a PET and PP base for POPUP applications. Nice semi-matt finish with a silver backing. This heavy 340 micron, <code>%ulti-layer+film</code> has , has excellent stiffness and no transmit of light. Product has good lamination properties.

Qualifications

- A smooth semi-matt finish
- PET & PP base material
- Print side: semi-matt white surface
- Reverse side: Silver backing
- Available in 36+x 30m
- Core size: 3+

Details

- Suitable printing condition: temperature 15-30°C / humidity 30-60%
- Dye based inks and pigmented inks are compatible
- Over laminating, the printer material prolong the life of the print
- Ambient temperature and weather can affect the condition of the product

Applications

- Pop-up systems
- Trade show displays
- Shop displays

Physical Properties

Quality	PET & PP
Weight	415g/m²
Thickness	340 µm test method: ASTM D645
Print side	Semi- Matt finish
Reverse side	Silver Blockout backing
L.a.b.	85/0 /-5 test method: ANSI T (D50/2º/Abs/No)
yellowness	35 test method: ASTM D1925
glossiness	10/15 test method: ASTM 2457

Compatibility

Hewlett Packard Roland Mimaki Mutoh And more... Mild solvent
Eco solvent

Make your own practical test to be sure it reaches your quality standard.

For all- and latest information see our Compatibility List.

Printing guidelines

Ink restrictions and heater settings have to be set for specific printer ink combinations to obtain the best results.

Colour profiles

ATgraphix develops high quality ICC colour profiles for the divers printing media's. We work with specialists who can produce your profile if its not direct available from our library. Please contact us for the possibilities.

Storage conditions

1 year under normal conditions (10. 25°C at a relative humidity of 50 %). Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place.

Environment

The media and final prints can be disposed as polyester. Material is suitable for recycling. Please consult local recycle resources.

Data presented in this product information serve only as a guide-line for compatibility and use. ATgraphix will assume no liability in connection with any use of this information. Technical specifications are subjected to change without prior notice. ATgraphix, The Netherlands. www.atgraphix.com