

Product: Polyjet Monomeeri Valkoinen

Product Description:

Monomeric REACH and RoHS compliant PVC film suitable for use in a wide variety of applications with flat and slightly curved surfaces. Suitable for colour intensive and brilliant prints for short to medium term advertisement both indoor and outdoor. High adhesion to a wide variety of substrates including varying plastics, foamex, glass and aluminium. Excellent printing performance on a wide variety of solvent, eco-solvent, latex and UV digital print machines

Product structure:

Support	PVC film, 100 µm, white, glossy
Interliner	One side siliconised surface-coated paper, white, 120 g/m ²
Adhesive	pure polyacrylic, permanent, transparent
Total Thickness	0.12 mm
Adhesive weight	20 g/m ²

Characteristics:

		Average Value	Test Method
Adhesion on steel:	(after 20 min.)	8 N/25mm	AFERA 5001
Adhesion on steel:	(after 24 h)	11 N/25mm	AFERA 5001
Dimensional Stability:	MD	< -2.7%	FTM 14
Dimensional Stability:	CD	< 0%	FTM 14
Flammability:		B1	DIN 4102

Sesoma Oy
Mittalinja 5
01260 Vantaa

Myynti: 020 745 9620
Sähköposti: sesoma@sesoma.fi